

# KODAK EKTALITE

## Slide Projectors

With Extra Bright  
Lamp Module  
30% more light!



Products

*Professional projection quality at a reasonable price.*

*Sturdy mechanical system with 82 V halogen cold-light lamp requiring no adjustments.*

*Convenience and ease of use put you among the round tray professionals.*

The reasonably priced **KODAK EKTALITE 500 Slide Projector** puts you in a position to make single-projector presentations of professional quality. Its sturdy mechanical system and simplicity of use are among the attractions of this projector.

The switchable autofocus and a built-in timer are the attraction of the **KODAK EKTALITE 1500 Slide Projector**. Both projectors are ideal for mobile or stationary use in all fields of active learning: in schools, universities, and seminar and conference rooms.

With the dissolve capability of the **KODAK EKTALITE 2000 Slide Projector** you can make your presentations even more effective and professional. The built-in 12-pin DIN plug allows you to connect with a number of dissolve controls available on the market.

The standard production, switchable autofocus gives you a big advantage in the presentation of glassless framed slides. With its built-in timer, this projector can be used to give self running slide shows such as those at trade fairs and museums.

Thanks to the new Extra Bright Lamp Module all projectors achieve a 30% higher lightoutput than compared to former models.

The KODAK EC Stack Loader gives you the advantage of quick projection of your slides without the need to arrange them beforehand in the tray. A stack of thin glassless slides is loaded directly into the stack loader.

Additional features of the KODAK EKTALITE Projectors ensuring ease of use are the automatic shutter (no-slide-no-light) which operates when the tray compartment is empty and does not allow any dazzling projection light on the screen, and a quick tray release which allows removal of the slide tray in any position. A cable remote control with LED display and an IR remote control are available.

You can choose from among a wide range of KODAK Slide Projection Lenses for optimal projection results.

Kodak

## Technical Data at a glance

| KODAK EKTALITE Slide Projector                                                                                                              |                                   | 500 | 1500 | 2000 |
|---------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-----|------|------|
| 12-pin DIN socket for external control (dissolve)                                                                                           |                                   | -   | -    | ■    |
| Autofocus (switchable)                                                                                                                      |                                   | -   | ■    | ■    |
| Timer (3 to 22 seconds)                                                                                                                     |                                   | -   | ■    | ■    |
| Economy lamp setting                                                                                                                        |                                   | -   | ■    | ■    |
| Slide registration vertical                                                                                                                 |                                   | -   | ■    | ■    |
| Slide registration horizontal                                                                                                               |                                   | ■   | ■    | ■    |
| Slide format 24 x 36 mm                                                                                                                     |                                   | ■   | ■    | ■    |
| Reading light to aid operator in darkened rooms                                                                                             |                                   | -   | ■    | ■    |
| Compatible with 80 or 140 Kodak Slide Trays and KODAK Stack Loader                                                                          |                                   | ■   | ■    | ■    |
| 6-pin (DIN) remote socket                                                                                                                   |                                   | ■   | ■    | ■    |
| Single Extra Bright Lamp Module offers a 30% higher lightoutput than compared to former modules. The module enables quick lamp replacement. |                                   | ■   | ■    | ■    |
| Slide select bar for quick tray change even when the projector is switched off                                                              |                                   | ■   | ■    | ■    |
| No-slide-no-light feature (automatic shutter to block light beam if no slide is in the gate)                                                |                                   | ■   | ■    | ■    |
| Convenient cable storage                                                                                                                    |                                   | ■   | ■    | ■    |
| Textured, non varnished high impact thermoplastic housing                                                                                   |                                   | ■   | ■    | ■    |
| 1,2 sec slide change time                                                                                                                   |                                   | ■   | ■    | ■    |
| Compatible with gear rack lenses (such as KODAK EKTAPRO Projektion FF Lenses)                                                               |                                   | ■   | ■    | ■    |
| Projection lamps                                                                                                                            | EXR 82 V/ 35 h/300 W              | ■   | ■    | ■    |
|                                                                                                                                             | FHS 82 V/ 70 h/300 W              | ■   | ■    | ■    |
|                                                                                                                                             | EXY 82 V/ 200 h/250 W             | ■   | ■    | ■    |
| Height adjustment                                                                                                                           | > 16°                             | ■   | ■    | ■    |
| Power consumption:                                                                                                                          | approximately 400 W               | ■   | ■    | ■    |
| Dimensions (L x W x H)                                                                                                                      | 295 x 328 x 119 mm (without tray) | ■   | ■    | ■    |
| Weight:                                                                                                                                     | 7000 g                            | ■   | ■    | ■    |
| Voltage: Multivoltage selector (100, 115, 130, 220, 230 and 240 V (both 50 and 60 Hz))                                                      |                                   | ■   | ■    | ■    |
| Fixed voltage                                                                                                                               | 230 V 50 Hz                       | ■   | -    | -    |
| Warranty:                                                                                                                                   | 1 year                            | ■   | ■    | ■    |



**KODAK EC Stack Loader (accessory) for rapid projection of thin glassless slides**



**12-pin DIN Socket for connection of dissolve units**



**KODAK EKTALITE 2000 Slide Projector with KODAK EKTALITE IR Remote Control**



For more information on this or any other KODAK PRESENTATION TECHNOLOGIES Product, check the Internet at [www.kodak.com/go/projectors/](http://www.kodak.com/go/projectors/) or call

- in Austria/Österreich - 01-795-67000
- in Belgium/Belgique - 02-713-1398
- in Denmark/Danmark - 3848-7088
- in Finland/Soumi - 0800-11-8043
- in France - 0141-918578
- in Germany/Deutschland - 069-9509-6055
- in Ireland/Eire - 01-402-6815
- in Italy/Italia - 02-696-33205
- in Netherlands/Nederlands - 020-346-9128
- in Norway/Norge - 2316-2088
- in Spain/Espana - 91-406-9130
- in Sweden/Sverige - 08-587-70305
- in Switzerland/Schweiz/Suisse - 01-838-5358
- in UK (National Line) - 0870-606-1031

Calls will be charged at a National Rate

- other countries - call the UK on 0044-870-606-1031

KODAK, CAROUSEL, EKTALITE, EKTAPRO and S-AV are registered trade marks.  
Publ. No 200 00 0199, G&S 0425/99  
Printed in Germany.



**Presentation  
Technologies**

Dealer Address:

**Kodak**

EKTALITE Products